

Models

911 GT2	
Engine Concept	Water-cooled, rear-mounted, horizontally opposed "Boxer" six-cylinder
Construction	Engine block and cylinder heads formed in aluminum
Valvetrain	Four overhead camshafts, four valves per cylinder, variable intake valve timing (VarioCam), hydraulic valve play compensation
Lubrication	Dry-sump
Management	Motronic® with six coils, sequential multipoint fuel injection
Electrical System	12 volt, 2100 watt alternator, 60 Ah battery
Fuel	Premium unleaded
Bore	3.94 in. (100 mm)
Stroke	3.01 in. (76.4 mm)
Displacement	3600 cc
Max. Horsepower	530 hp at 6500 rpm
Max. torque (lb.ft.)	505 lb.ft. at 4500 rpm
Engine redline	6750 rpm
Compression ratio	9.0:1
Output per liter	147.2 HP
Drivetrain	all-wheel drive
Power unit	Engine and transmission bolted together to form common drive unit, engine power transmitted via driveshafts
Gearbox	Manual
Gear Ratios	
1	3.15
2	1.89
3	1.4
4	1.09
5	0.89
6	0.73
R	2.86
Final Drive	
Rear Axle	3.44
Front Axle	
Clutch Diameter	9.45 in. (240 mm)

Body	Monocoque structure, lightweight, hot-galvanized all-steel body shell, front lid and doors made of aluminum, full-size frontal, side and head airbags for driver and passenger, two-seater
Drag Coefficient	0.32
Front Suspension	Independent, Porsche optimized McPherson spring strut axle, wheels suspended on track control arms, longitudinal arms and spring struts, twin-sleeve gas-charged shock absorbers with active control (PASM)
Rear Suspension	Independent, five arms configuration, coil springs, single-sleeve gas-charged shock absorbers with active control (PASM)
Brakes	Two-circuit system with separate brake circuits on each axle, vacuum brake servo standard integrated anti-lock control and Traction Control
Front	Six-piston aluminum monobloc calipers with cross-drilled inner-vented brake discs
Rear	Four-piston aluminum monobloc calipers with cross-drilled inner-vented brake discs
Front Brake Discs	380 mm x 34 mm (14.96 in. x 1.34 in.)
Rear Brake Discs	350 mm x 28 mm (13.78 in. x 1.1 in.)
Wheels and Tires	
Front	8.5J x 19 with 235/35 ZR 19
Rear	12J x 19 with 325/30 ZR 19
Dimensions	
Front Track	59.65 in. (1515 mm)
Rear Track	61.02 in. (1550 mm)
Wheelbase	92.52 in. (2350 mm)
Length	176.93 in. (4494 mm)
Width	72.9 in. (1852 mm)
Height	50.51 in. (1283 mm)
Luggage Capacity	
Front Trunk	3.71 cu. ft. (105 liter)
Behind Front Seats	7.24 cu. ft. (205 liter)
Fuel Tank Capacity	23.8 US gal. (90 liter)
Curb Weight	
[lbs. / kg]	3,175 / 1,440
Fuel economy city/hwy	16/23
Top Track Speed	204 mph (329 km/h)
Acceleration	
0-60mph (0-96 km/h)	3.6 sec.
0-99 mph (0-160 km/h)	7.4 sec.