

Models

	911 Targa 4		911 Targa 4S	
Engine Concept	Water-cooled, rear-mounted, horizontally "boxer" six cylinder			
Construction	Engine block and cylinder heads formed in aluminum			
Valvetrain	Four overhead camshafts, four valves per cylinder, variable intake valve timing and lift control (VarioCam Plus), hydraulic valve play compensation			
Intake System	Direct Fuel Injection (DFI)			
Lubrication	Integrated dry-sump			
Management	Motronic® with six coils, sequential multipoint fuel injection			
Electrical System	12 volt, 2100 watt alternator, 70 Ah battery			
Fuel	Premium unleaded			
Bore	3.82 in. (97 mm)		4.02 in. (102 mm)	
Stroke	3.21 in. (81.5 mm)		3.05 in. (77.5 mm)	
Displacement	3614 cc		3800 cc	
Max. Horsepower	345 hp at 6500 rpm		385 hp at 6500 rpm	
Max. torque (lb.ft.)	288 lb.ft. at 4400 rpm		310 lb.ft. at 4400 rpm	
Engine redline	7500 rpm		7500 rpm	
Compression ratio	12.5:1		12.5:1	
Output per liter	95.5 hp		101.3 hp	
Drivetrain	all-wheel drive			
Power unit	Engine and transmission bolted together to form one drive unit; power transmission via double universal shafts to rear wheels			
Gearbox	Manual	PDK	Manual	PDK
Gear Ratios				
1	3.91	3.91	3.91	3.6
2	2.32	2.29	2.32	2.19
3	1.56	1.65	1.56	1.41
4	1.28	1.30	1.28	1.00
5	1.08	1.08	1.08	0.83
6	0.88	0.88	0.88	0.88
7	--	0.62		0.62
R	3.59	3.55	3.59	3.17
Final Drive				
Rear Axle	3.44	3.44	3.44	3.56
Front Axle	3.33	3.45	3.33	3.45
Clutch Diameter	9.45 in. (240 mm)	7.95 in. (202 mm)/ 6.02 in. (153 mm)	9.45 in. (240 mm)	7.95 in. (202 mm)/ 6.02 in. (153 mm)

Body	Monocoque structure, lightweight all-steel body hot-galvanized on all sides; full-size frontal, side and head airbags for driver and passenger; number of seats 2+2.						
Drag Coefficient	0.30						
Front Suspension	Independent, Porsche optimized McPherson spring strut axle, wheels suspended on track control arms, longitudinal arms and spring struts, twin-sleeve gas-charged shock absorbers with active control (PASM) on Targa 4S						
Rear Suspension	Independent, five arms configuration, coil springs, single-sleeve gas-charged shock absorbers with active control (PASM) on Targa 4S						
Brakes							
Front	Four-piston aluminum monobloc calipers with cross-drilled inner-vented brake discs						
Rear	Four-piston aluminum monobloc calipers with cross-drilled inner-vented brake discs						
Front Brake Discs	318mm x 28mm (12.52 in.x 1.10 in.)			330mm x 34mm (12.99 in. x 1.34 in.)			
Rear Brake Discs	299mm x 24mm (11.78 in. x 0.95 in.)			330mm x 28mm (12.99 in. x 1.10 in.)			
Wheels and Tires							
Front	8J x 18 with 235/40 ZR 18			8J x 19 with 235/35 ZR 19			
Rear	11J x 18 with 295/35 ZR 18			11J x 19 with 305/30 ZR 19			
Dimensions							
Front Track	58.6 in. (1488 mm)						
Rear Track	60.9 in. (1548 mm)						
Wheelbase	92.52 in.						
Length	175.6 in.						
Width	72.9 in.						
Height	51.6 in.			51.2 in.			
Luggage Capacity	3.71 cu.ft						
Fuel Tank Capacity	17.7 gal.						
Curb Weight	Manual	PDK	PDK w/Sport Chronos Package Plus	Manual	PDK	PDK w/Sport Chronos Package Plus	
[lbs. / kg]	3373 lbs.		3439 lbs.		3395 lbs.		3461 lbs.
Fuel economy city/hwy	18/25		18/26		18/25		18/27
Top Track Speed	177 mph		175 mph		185 mph		183 mph
Acceleration							
0-60mph (0-96 km/h)	5.0 sec.	4.8 sec.	4.6 sec.	4.7 sec.	4.5 sec.	4.3 sec.	